

HKS	Garrett	Tapered Tip Angle	BCCW Blade	Inducer	Exducer	Superback	Overall Height	Bore Size
GT2530 (63 TRIM)	GT2860R	30°	6+6	47.71	60.13	2.3	24.60	5.99
GT-RS (52 TRIM)	GT2871R	30°	6+6	51.17	70.98	2.32	34.63	5.99
		18°	11+0	51.17	70.98	2.32	34.63	5.99
GT2835 (56 TRIM)	GT3071R	30°	6+6	53.11	70.98	2.32	34.63	5.99
			11+0	53.11	70.98	2.32	34.63	5.99
GT3037 (56 TRIM)	GT3076R	30°	6+6	57.04	76.13	2.36	34.63	5.99
			11+0	57.04	76.13	2.36	34.60	5.99
GT3540 (56 TRIM)	GT3582R	18°	6+6	61.33	82.00	2.35	35.68	6.35
			11+0	61.33	82.00	2.35	35.68	6.35
	GTX3582R GEN II (64 TRIM)	13.6°	10+0	65.70	82.46	2.36	37.82	6.35
		30°	10+0	65.70	82.46	2.36	37.82	6.35
	GTX3584R GEN II (64 TRIM)	13.6°	10+0	67.30	84.44	2.36	38.62	6.35
		30°	10+0	67.30	84.44	2.36	38.62	6.35
TRUST	MHI	Tapered Tip Angle	BCCW Blade	Inducer	Exducer	Superback	Overall Height	Bore Size
TD05-18G	49179-43300	30°	6+6	50.39	68.01	2.90	35.00	6.50
			11+0	50.39	68.01	2.90	35.20	6.50
TD06-20G	49179-43400	30°	6+6	52.56	68.01	2.90	35.00	6.50
			11+0	52.56	68.01	2.90	35.00	6.50
TD06-20G Upgrade		30°	6+6	56.58	73.04	2.90	35.04	6.50
TD-07S		30°	6+6	60.50	78.00	2.70	34.13	7.00